

Product Data Sheet

OCTACAT T9

STANNOUS OCTOATE

PRODUCT DESCRIPTION

OCTACAT T9 is a polyurethane catalyst. It was designed for using in many areas. It has no influence for foam property when it stays in foam which plays a role of age inhibitor.

APPLICATIONS

OCTACAT T9 is a polyurethane catalyst which is mainly used in soft lump foam production. Also, it can be used in the polyurethane coating and elastomer areas.

For more product information please contact OCTAPUR Kimya San ve Tic AŞ

TYPICAL PRODUCT PROPERTIES

Appearance	Colorless to light yellow transparent liquid	visual
Viscosity (25 °C)	500 max	mPa.s
Tin Content	≥ 28	%
Density (25 °C)	1.25	g/ml
Stannous Content	27.8	%

PACKAGING AND STORAGE

We recommend that our catalysts be stored in a dry and cool area under appropriate ventilation conditions. Each container should be closed tightly to avoid contamination with moisture or other negative influences, which could change the products' performance in the end use. And it can be stored 24 months at least.

25KG/Pail, 32Pails can be made on one pallet; 250KG/Drum, 4 drums can be made on one pallet.

OCTAPUR Kimya San. ve Tic. A.Ş.

Barbaros Mah Begonya Sok No:1/2 Nidakule Ataşehir / İstanbul

www.octapur.com | info@octapur.com

Version 1.1